

PRODUCT-DETAILS

OVR T2 40-275

OVR T2 40-275 Surge Protective Device



General Information

Extended Product Type	OVR T2 40-275
Product ID	2CTB804201R1100
EAN	3660308519412
Catalog Description	OVR T2 40-275 Surge Protective Device
Long Description	B751941

Technical

Type of Low Voltage Distribution System	TT TN-C TN-S
Nominal AC Voltage of the System (U _n)	230 / 400 V
Number of Protected Poles	1
Arrester Class	II
Product Main Type	T2
Standards	IEC 61 643-11 / EN 50539-11
Version	Fix
Discharge Current	Nominal 20 kA Maximum 40 kA Total 40 kA

Maximum Continuous Operating Voltage (U_c)	(L-PE) 275 V (L-L) 275 V (L-N) 275 V (N-PE) - V
Voltage Rating DC	350 V
Voltage Protection Level (Up)	(L-N) - kV (N-PE) - kV (L-PE) 1.4 kV
Short Circuit Withstand I_{cc}	50 kA
Temporary Overvoltage Test Value (U_T)	337 V
Short-Circuit Protective Devices	gG Type Fuses \leq 63 A gL Type Fuses \leq 63 A Curve B Breakers \leq 125 A Curve C Breakers \leq 125 A
Product Name	Surge Protective Device
Suitable For	To protect the systems against the transient overvoltage (lightning)

Dimensions

Product Net Width	17.8 mm
Product Net Depth / Length	58 mm
Product Net Height	88 mm
Product Net Weight	0.12 kg

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	117 mm
Package Level 1 Depth / Length	25 mm
Package Level 1 Height	82 mm
Package Level 1 Gross Weight	150 g
Package Level 1 EAN	3660308519412

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85363090

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CTC436004G1701
Instructions and Manuals	2CTC432018M1701

Popular Downloads

Data Sheet, Technical	2CTC432189D1701
-----------------------	-----------------

